



QUOTATION REQUEST FORM

Customer: _____ Contact: _____
 Phone #: _____ Fax #: _____
 Email: _____ Job Name: _____

Date: _____
 Bid Due By: _____
 Expected Delivery Date: _____
 FOB: _____

Phone: (888)-454-2888 Fax: (888)-454-2889 Email: info@doormerica.com

(Delivery Address / Zip Code Required for Freight Quotes)

Door Construction Spec: FP - Fiber Pine (Hollow Core) FJ - Finger Joint (Hollow Core) E - Economy S - Standard HD - Heavy Duty EHD - Extra Heavy Duty MC - Mineral Core	Order Coordinated By: Distributor Manufacturer <hr/> LEED: Leed for Schools MR 4 - Recycled MR 5 - Regional Materials MR 6 - Rapidly Renewable MR 7 - FSC Certified IEQ 4.4 - No Added UF	Industry Standard: AWI/WI: Premium Custom Economy WDMA: Standard Heavy Extra Heavy	Factory Finishing: (All Prefinish includes Protective Peel Coat) Prime APF Standard Stain APF Clear APF Custom Stain (Min 25 Doors)
			Louvers: Cutout Only Metal AFDL
			Light Openings: Nonrated: Cutout Only Flush Molding(W-9) Lip Molding(W-7) MVP Lo-Pro Rated: Cutout Only Flush Molding (W-9)(20MIN) Lip Molding (W-7)(20MIN) Flush Molding (W-9)(45-90MIN) Lip Molding (W-7)(45-90MIN) MVP Lo-Pro
Species: _____ Special Match: _____ Grade: Paint Grade A Grade AA Grade Cut: Rotary Plain Sliced Quartered Rift (Slip Matched) Assembly: Running Balanced Center Match: Book Slip Random			Packaging: I.D Marking Polybag (Raw Only)
Plastic Laminate Doors: Manufacturer: _____ Color #: _____ Color Name: _____ Stiles: Raw Stiles Plastic Laminate Applied After Faces			Fire Test Method: Neutral Pressure ITS - WH CSFM Positive Pressure Category A Positive Pressure Category B Metal Edge & Astragal
Molded Panel: Name of Design: _____			

Door QTY	Pair Match	Core & Rating	Size (in feet) Width x Length	Thick	Lite/Louwer	Hinges	Locks				Exit Devices			Strike	Flush bolts	Blocking			Special Notes & Instructions:	
							Cyl	Lever	Mortise	Card	SVR	Rim	CVR			Top	Bottom	Lock		

