

FLUSH HOLLOW CORE



<b>Specifications:</b>	3 & 5 Ply construction. Meets or exceeds industry standards of WDMA I.S.1.
<b>Lay Up Method</b>	Loose
<b>Maximum Sizes:</b>	Width - 4/0. Length depends on face (See faces below for available length)
<b>Thickness:</b>	1-3/8" and 1-3/4" ONLY
<b>Stiles:</b>	MDF available on MDF type skins, Only 1-3/8" Thickness & 6/8 Length. Softwood available on all skin types 1-3/8" and 1-3/4" Thickness. Width = 1" Nominal, 13/16" Minimum after prefit size.
<b>Rails:</b>	1-3/8" Thickness = MDF, 1-5/8" Nominal, 1" Minimum after undercut 1-3/4" Thickness = MDF, 2-1/4" Nominal, 1" Minimum after undercut
<b>Core:</b>	Cellular Honeycomb with 5" Hexagonal cells.
<b>Lock Blocks:</b>	Double 3" x 20" Particleboard (28lb) as standard.
<b>Faces:</b>	Lauan (Okoume) - Raw, 2 ply, 8/0 Maximum. RN Birch - Raw, 2 ply, 1/64" Face veneer thickness, 8/0 Maximum. PS Red Oak - Raw, 2 ply, 1/64" face veneer thickness, 8/0 Maximum. MDF - Primed and Raw, Single Ply, 10/0 Maximum. Embossed MDF - Primed and Prefinished, Single Ply, 8/0 Maximum.
<b>Adhesive:</b>	Type-1 PVA, Interior installation only.
<b>Machining:</b>	To Specification
<b>Lites:</b>	To specification. Blocking only upon request.
<b>Louvers:</b>	To specification. Blocking only upon request.
<b>Acoustical Rating:</b>	N/A
<b>Warranty:</b>	Standard two year. See limited warranty for details. *No warranty for Telegraphing*
<b>Description</b>	(FP-1-3/8) = 1-3/8" Thick, MDF Stiles
<b>Abbreviations:</b>	(FJ-1-3/8) = 1-3/8" Thick, FJ Softwood Stiles (SWE-1-3/8) = 1-3/8" Thick, Clear Softwood Stiles (FJ-1-3/4) = 1-3/4" Thick, FJ Softwood Stiles (SWE-1-3/4) = 1-3/4" Thick, Clear Softwood Stiles
<b>Recommended Use:</b>	Residential and Light Commercial

01