

MOLDED PANEL HOLLOW CORE



<b>Specifications:</b>	3 Ply construction. Meets or exceeds industry standards of WDMA I.S.1.
<b>Lay Up Method</b>	Loose
<b>Maximum Sizes:</b>	Width - 3/0 Length - 8/0 *Certain styles only*
<b>Thickness:</b>	1-3/8" and 1-3/4" ONLY
<b>Stiles:</b>	MDF on only 1-3/8" Thickness & 6/8 Length. FJ Softwood option on 1-3/8" and 1-3/4" Thickness, to 8/0 length. Width = 1" Nominal, 13/16" Minimum after prefit size.
<b>Rails:</b>	1-3/8" Thickness = MDF, 1-5/8" Nominal, 1" Minimum after undercut 1-3/4" Thickness = MDF, 2-1/4" Nominal, 1" Minimum after undercut 2" Nominal Bottom rail available on 1-3/8" Thickness (DBR)
<b>Core:</b>	Cellular Honeycomb build up pads.
<b>Lock Blocks:</b>	Double 3" x 10" Particleboard (28lb) as standard.
<b>Faces:</b>	Primed MDF Molded Panel, Single ply
<b>Adhesive:</b>	Type-1 PVA, Interior installation only.
<b>Machining:</b>	To Specification
<b>Lites:</b>	N/A
<b>Louvers:</b>	N/A
<b>Acoustical Rating:</b>	N/A
<b>Warranty:</b>	Standard two year. See limited warranty for details. *No warranty for Telegraphing*
<b>Description</b>	(FP-1-3/8) = 1-3/8" Thick, MDF Stiles
<b>Abbreviations:</b>	(FJ-1-3/8) = 1-3/8" Thick, FJ Softwood Stiles (FJ-1-3/4) = 1-3/4" Thick, FJ Softwood Stiles
<b>Recommended Use:</b>	Residential and Light Commercial

02

\*See molded skin selection guide for all panel elevation designs.