

DOOR SPECIFICATIONS

BIFOLDING DOORS



Specifications:	Bifolding doors are available in the following door types.
	Hollow Core Flush, Hollow Core Molded Panel, Molded Panel Economy
	Particleboard Core, Flush Economy Particleboard Core, Flush Standard
	Particleboard Core
Maximum Sizes:	See Specific Door Type.
Thickness:	See Specific Door Type.
Stiles:	1" Wood
Rails:	1-5/8" Wood on 1-3/8" Thickness.
	2-1/4" Wood on 1-3/4" Thickness.
Core:	See Specific Door Type.
Lock Blocks:	See Specific Door Type.
Faces:	See Specific Door Type.
Adhesive:	Type-1 PVA, Interior installation only.
Machining:	N/A
Lites:	N/A
Louvers:	N/A
Acoustical Rating:	N/A
Warranty:	Standard two year. See limited warranty for details.(See Specific Door Type)
Description	See Specific Door Type.
Abbreviations:	
Recommended	Residential and Light Commercial
Use:	
Hardware:	US 15 Hinges - Edge mount window hinge on Hollow Core
	3-1/2" full mortise hinge on Solid Core
	Standard Duty Track & Hardware - Stanley #2900 Series.
	Heavy Duty Track & Hardware - Stanley #2700 Series.

0



^{*} All bifolds are boxed with track and hardware. Non boxed (bulk packaging) available on request.